

# Specify and Install 440 SoundBarrier with Confidence

Use 440 SoundBarrier in tested and approved fire rated floor and wall assemblies that carry the UL (Underwriter's Laboratory) hourly ratings.

Fire Ratings are assigned to entire floor/ceiling and wall assemblies – not to individual product components of those systems.

## U.L. FIRE RESISTANCE RATING DESIGN NUMBERS

### Floor/Ceiling Assemblies (CERZ Category) in which is 440 listed

Structural Steel Members (Steel Joists)											
G203	G208	G227	G228	G229	G243	G268	G301	G524	G525	G531	J201
L524	L527	L543	L549	L551	L552	L556	L565	M513	M534	M536	
Wood Joist											
L210	L501	L502	L503	L504	L505	L506	L507	L508	L509	L510	L511
L510	L511	L512	L513	L514	L515	L516	L517	L519	L520	L522	L523
L522	L523	L525	L526	L532	L533	L535	L536	L537	L539	L540	L541
L540	L541	L545	M504	M530							
Structural Wood Members (I-Joists)											
		L518	L538	L547	L556	L570					
Parallel Chord Truss (Open Web Joists)											
L521	L528	L529	L534	L542	L546	L550	L558	L562	L563	L576	L577
L576	L577	L587	M503								

*440 SoundBarrier is One Conventional, High-Performance Green Product That Lasts In Floors, Walls and Ceilings*

### Wall Assemblies (CERZ Category) in which is 440 listed

Wood Studs							
U305	U309	U339	U340	U341	U390	V305	V310
Steel Studs							
U411	U465	V446	V448	W461			

*Made of 98% Recycled Content • Twice the R-Value of Wood*

**HOMASOTE®**

**Sensible. Sound.  
Solutions.**

800-257-9491 • Technical Support call Ext. 1332 or e-mail [techhelp@homasote.com](mailto:techhelp@homasote.com)

[www.homasote.com](http://www.homasote.com)