



*Sensible. Sound.
Solutions.*



932 Lower Ferry Road • Box 7240 • West Trenton, New Jersey 08628-0240 • +1-609-883-3300 • Fax +1-609-883-3497

MANUFACTURER

Homasote Company
932 Lower Ferry Road
West Trenton, New Jersey 08628
800-257-9491, Ext: 1332
sales@homasote.com

DESCRIPTION

NCFR Homasote panels are made from recycled paper fibers, 2% paraffin wax, less than 0.1% copper metaborate and aluminum trihydrate. The substrate is free of asbestos, formaldehyde, urea and phenolic additives.

NCFR Homasote is a Class A fired-rated (Flame Spread 20) molded, recycled post-consumer paper, cellulose fiber panel that is manufactured in a thickness of 1/2" and in a nominal sizes of 4'x 8'.

NCFR Homasote is a Class A substrate when tested as per ASTM E84.

USES

NCFR Homasote is used as a finish wall surface when Class A furnishings are required. It can have fabric adhered to it.

NCFR Homasote is also used as a component in our Fire Rated structural roofing products.

NCFR Homasote can also be used in Type I and Type II (non-combustible) construction under Section 603 of the IBC relating to acoustical insulation products.

LIMITATIONS

NCFR Homasote, along with all attendant finish wall or floor products must be installed in accordance with pertinent manufacturer's published installation instructions.
<http://www.homasote.com/products/440-soundbarrier>

TECHNICAL DATA

NCFR Homasote has been tested under the auspices of the following ASTM Standards:

ASTM C208
ASTM C209
ASTM D1037
ASTM E84
ASTM E119

For comprehensive technical specifications please visit:
http://www.homasote.com/assets/files/3part/n-cfr-homasote_3partspecifications.pdf

For technical assistance please call 800-257-9491, ext: 1332 or visit
techhelp@homasote.com

SUBMITTAL APPROVALS

Job Name: _____

Contractor: _____

Date: _____