



**Sensible. Sound.
Solutions.**



932 Lower Ferry Road • Box 7240 • West Trenton, New Jersey 08628-0240 • +1-609-883-3300 • Fax +1-609-883-3497

MANUFACTURER

Homasote Company
932 Lower Ferry Road
West Trenton, New Jersey 08628
800-257-9491, Ext: 1332
sales@homasote.com

DESCRIPTION

PINnacle Tackboard panels are made from 98% recycled paper fibers, 2% paraffin wax, and less than 0.1% copper metaborate. The substrate is free of asbestos, formaldehyde, urea and phenolic additives.

PINnacle Tackboard is a lightweight decorative tackable panel with a density of 25 to 29 pounds per cubic foot that is manufactured in a thickness of 1/2" and in a nominal size of 4' x 8'. The PINnacle Tackboard panels are finely sanded with a suede-like feel to the touch.

PINnacle Tackboard is a Class C substrate as tested as per ASTM E-84.

PINnacle NCFR is a Class A substrate as tested per ASTM E-84

USES

PINnacle Tackboard is an industry standard decorative tackable panel for interior and protected exterior use.

LIMITATIONS

PINnacle Tackboard must be installed in accordance with pertinent manufacturer's published installation instructions.
<http://www.homasote.com/assets/files/installation/pinnacle.pdf>

TECHNICAL DATA

PINnacle Tackboard is the prefinished version of 440 SoundBarrier and thus has been tested under the auspices of the following:

ASTM E84
ASTM C208
ASTM C209
ASTM D1037

ICC Evaluation Report ESR-1374

FSC Certificate SGSNA-COC-005682

For comprehensive technical specifications please visit:
http://www.homasote.com/assets/files/3part/pinnacle440_3partspecifications.pdf

For technical assistance please call 800-257-9491, ext:1332 or visit
techhelp@homasote.com

SUBMITTAL APPROVALS

Job Name: _____

Contractor: _____

Date: _____